



American Recycling Center, Inc.



EQUESTRIAN ARENA FOOTING

Application & Installation



SURFACE PREPARATION

Proper drainage and leveling of your existing surface is highly recommended. It is imperative to have a solid, well-constructed base. Should you have questions, contact us.

PRICING & DELIVERY

Pricing: Pricing is based on quantities ordered and is available upon request.
Delivery: Delivery will be based on mileage and best transportation quotes obtainable at time of shipment. Cost for delivery will be added to the total invoice.

PACKAGING

PremARC™ Arena Footing can be packaged two different ways to fit your specific needs:

1. 50 lb. Bags
2. 2,000 lb. Super Sacks

COVERAGE

PremARC™ Arena Footing works best when applied at 1" - 1-1/2" deep to a dustless sand, for both indoor and outdoor applications.
Length x Width of Arena = Sq. Ft.

- For 1" of PremARC™ Arena Footing, multiply Sq. Ft. By 2.49 lbs
- For 1-1/2" of PremARC™ Arena Footing, multiply Sq. Ft. By 3.7 lbs (Example: Arena: 66' x 200' = 13,200 sq. Ft. 13,200 sq. Ft x 2.49 lbs = 32,868 lbs of PremARC™ Arena Footing needed)

INSTALLATION INSTRUCTIONS

1. PremARC™ Arena Footing should be dumped throughout the arena and spread evenly with a front bucket, rear blade, or rake.
2. After the material is dumped, it can be mixed in with a drag or naturally from normal use.

NOTE: PremARC™ Arena Footing is commonly delivered in a semi-truck & trailer. It is important to confirm the delivery location has access available for a 75 foot long, 13 foot high semi. Also confirm that equipment will be available at delivery that can lift a 2,200 lb pallet.